## **©OUTLANDER™ MAX XT 570 T**

- Rotax® V-Twin engine
- Anti-Lock Braking System (ABS)
- Intelligent Throttle Control (iTC™) with riding modes
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS™)
- 1,361 kg (3,000 lbs) WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- · Painted plastics for premium look
- 12-in. cast-aluminum wheels
- 25-in. Carlisle Trail Wolf tires

- Torsional Trailing arm Independent (TTI) rear suspension
- · Wind deflectors
- Steel racks with LinQ quick-attach accessory system and a combined 163.3 kg
- 10.9 L water-resistant rear compartment
- Dynamic passenger comfort ergonomics
- Multiposition passenger handgrips
- · Raised floorboards



Hyper Silver

<b>ENGINES</b>	570
Туре	48 hp, Rotax V-twin, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC <sup>TM</sup> ) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	More than 60 km/h

турс	40 lip, Rotax v-twiii, liquid cooled
Fuel Delivery System	Intelligent Throttle Control (iTC <sup>TM</sup> ) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
Speed category	More than 60 km/h
SUSPENSIONS	

SUSPENSIONS	
Front Suspension	Double A-arm 22.9 cm travel
Front Shocks	0il
Rear Suspension	Torsional Trailing arm Independent (TTI) 22.4 cm travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
ABS	Standard

TIRES / WHEI	ELS
Front Tires	Carlisle Trail Wolf 25 x 8 x 12 in. (63.5 x 20.3 x 30.5 cm)
Rear Tires	Carlisle Trail Wolf 25 x 10 x 12 in. (63.5 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES	
LxWxH	231 x 116.8 x 133 cm
Wheelbase	149.9 cm
Ground Clearance	26.7 cm
Seat Height	85.8 cm
Dry Weight*	336 kg
Rack Capacity	Front: 54.4 kg Rear: 109 kg
Storage Capacity	Rear: 10.9 L
Towing Capacity	750 kg trailer with brakes and 335 kg trailer without brakes
Fuel Capacity	20.5 L

<b>FEATURES</b>			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer,	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
	trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Lighting	70 W from dual 35-W front light / brake light
		Seat	Convertible Rack System (CRS)
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Protection	Heavy-duty front & rear bumpers, wind deflectors

WARRANTY	
Factory	2 years



