©OUTLANDER™ X® mr 650

HIGHLIGHTS

- Rotax® V-twin engine
- Intelligent Throttle Control (iTC™) with riding
- New arched double A-arm front suspension with front sway bar
- 28-in. ITP Mega Mayhem† tires
- 12-in. cast-aluminum wheels
- Tri-Mode Dynamic Power Steering (DPS™)
- Visco-Lok[‡] QE auto-locking front differential
- Relocated radiator
- 3,000-lb (1,361 kg) WARN† winch with roller fairlead
- · Heavy-duty front bumper

- · Mud-riding footrests
- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control



Sunburst Yellow

ENGINE	650
Туре	59 hp, Rotax 649.6 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)

Туре	59 hp, Rotax 649.6 cc V-twin, snorkeled, liquid cooled with relocated radiator
Fuel Delivery System	Intelligent Throttle Control (iTC TM) with Electronic Fuel Injection (EFI)
Transmission	CVT, P / R / N / H / L, standard engine braking
Drive Train	Selectable 2WD / 4WD with Visco-Lok QE auto-locking front differential
Power Steering	Tri-Mode Dynamic Power Steering (DPS)
CHEDENCIONE	

Arched double A-arm with front sway bar
0il
Torsional Trailing arm Independent (TTI)
0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper

TIRES / WHEELS	
Front Tires	ITP Mega Mayhem† 28 x 8 x 12 in. (71.1 x 20.3 x 30.5 cm)
Rear Tires	ITP Mega Mayhem† 28 x 10 x 12 in. (71.1 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES		
LxWxH	224 x 123 x 128 cm	
Wheelbase	129.5 cm	
Ground Clearance	29.9 cm	
Seat Height	89.5 cm	
Dry Weight	396 kg	
Rack Capacity	Rear: 90 kg	
Storage Capacity	Rear: 21.4 L	
Towing Capacity	750 kg	
Fuel Capacity	20.5 L	

FEATURES			
Gauge	Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	3,000-lb (1,361 kg) WARN winch with roller fairlead	Anti-theft System	RF Digitally Encoded Security System (D.E.S.S.™)
Protection	Heavy-duty front bumper, mud-riding footrests, wind deflectors		

WARRANTY	
Factory	2 years

