agoutlander XT 650 T

HIGHLIGHTS

- Rotax[®] V-twin engine
- Intelligent Throttle Control (iTC™) with riding modes
- Anti-Lock Braking System (ABS)
- New arched double A-arm front suspension with front sway bar
- Continuously Variable Transmission (CVT) with engine braking
- Tri-Mode Dynamic Power Steering (DPS[™])
- 1,361 kg (3,000 lbs) WARN† winch with roller fairlead
- Heavy-duty front and rear bumpers
- Painted plastics for premium look
- 14-in. cast-aluminum wheels
- 26-in. ITP† Terracross radial tires

- Surrounding Spar Technology (SST) G2 frame with Geometric Contact Control
- Torsional Trailing arm Independent (TTI) rear suspension
- 625-W magneto
- High-strength, multifunction racks with LinQ[™] quick-attach accessory system
- 21.4 L water-resistant rear compartment



Black & Can-Am Red

TIRES / WHEELS	
Front Tires	ITP Terracross 26 x 8 x 14 in. (66 x 20.3 x 35.6 cm)
Rear Tires	ITP Terracross 26 x 10 x 14 in. (66 x 25.4 x 35.6 cm)
Wheels	14-in. cast-aluminum

DIMENSIONS / CAPACITIES			
L x W x H	218.4 x 121.9 x 126 cm		
Wheelbase	129.5 cm		
Ground Clearance	27.9 cm		
Seat Height	87.7 cm		
Dry Weight*	341 kg		
Rack Capacity	Front: 45 kg Rear: 90 kg		
Storage Capacity	Rear: 21.4 L		
Towing Capacity	750 kg trailer with brakes 395 kg trailer without brakes		
Fuel Capacity	20.5 L		

ENGINES	650		
Туре	59 hp, Rotax 649.6 cc V-twin, liquid cooled		
Fuel Delivery System	Intelligent Throttle Control (iTC™) with Electronic Fuel Injection (EFI)		
Transmission	CVT, P / R / N / H / L, standard engine braking		
Drive Train	Selectable 2WD / 4WD with Brake Traction Control (BTC)		
Power Steering	Tri-Mode Dynamic Power Steering (DPS)		
Speed category	More than 60 km/h		

SUSPENSIONS

Front Suspension	Arched double A-arm with front sway bar 23.3 cm travel		
Front Shocks	Oil		
Rear Suspension	Torsional Trailing arm Independent (TTI) 25.1 cm travel		
Rear Shocks	Oil		

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
_	

Rear	Single 214 mm ventilated disc brake with hydraulic twin-piston caliper
ABS	Standard

FEATURES

Gauge	auge Multifunction Digital: Speedometer, tachometer, odometer, trip & hour meters, fuel, gear position, 4 x 4 indicator, diagnostics, clock	Instrumentation	Lighter type DC outlet in console, standard connecto in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Standard
Winch	1,361 kg (3,000 lbs) WARN winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T-category features	Towing hitch with trailer plug, directional indicators, position lamps, mirrors, horn, lockable fuel cap and transmission	Protection	Heavy-duty front & rear bumpers, wind deflectors, mudguards

Factory 2 years

©2018 Bombardier Recreational Products Inc (BRP). All rights reserved. TM, [®] and the BRP logo are trademarks of Bombardier Recreational Products Inc. or its affiliates. In the U.S.A., the products are distributed by BRP US Inc. 'Visco-Lok is a trademark of GKN Viscodrive GmbH. 'All other trademarks are the property of their respective owners. BRP reserves the right, at any time, to discontinue or change specifications, prices, designs, features, models or equipment without incurring obligation. Some models depicted may include optional equipment. Read the vehicle Operator's Guide and watch the Safety DVD before driving. For your safety: wear a helmet, eye protection and other protective gear. Always remember that riding and alcohol/drugs don't mix. Passenger must be at least 12 years old and able to hold handgrips and plant feet while seated against the backrest. Never engage in stunt driving and avoid excessive speed.



Can-AmOffroad.com